

Q8 Formula F1

10W-50

Description

Supreme Performance Synthetic Engine Oil

Application

Extra high performance synthetic engine oil for passenger cars with normally aspirated or turbo charged gasoline or diesel engines. Specially recommended for highest performance, multi-valve engines with catalyst.

Specifications

- ACEA A3/B4
- API SM
- Farboud GTS and other high performance sports cars

Benefits

- Synthetic year round engine lubricant
- Excellent engine protection after cold starting
- Superior engine performance at extreme driving conditions
- Provides sustained high oil pressure
- Offers high oil film strength and thus limiting engine wear
- Good protection against rust and corrosion
- Low volatility by use of synthetic base oils provides minimized oil consumption
- Reduced environmental impact
- Prevents formation of black sludge
- Catalyst friendly lubricant

To be able to offer our clients products with constantly better characteristics, Kuwait Petroleum reserves the right, without further notice, to modify the specifications of its products at all times.

KUWAIT PETROLEUM INTERNATIONAL LUBRICANTS - NORTHWEST EUROPE

Technical Service
00800 786 45 787
www.Q8oils.com

Specifications

Specification	Method	Units	
SAE Viscosity Grade	-	-	10W-50
Absolute Density, 15 °C	D 4052	kg/m ³	855
Kinematic Viscosity, 100 °C	D 445	mm ² /s	17.6
Kinematic Viscosity, 40 °C	D 445	mm ² /s	119.0
Viscosity Index	D 2270		163
Apparent Viscosity, -25 °C	IP 383	mPa.s	5300
Borderline Pumping Temperature	D 3829	°C	-33
Pour Point	D 97	°C	-39
Flash Point	D 93	°C	215
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>=3.5

To be able to offer our clients products with constantly better characteristics, Kuwait Petroleum reserves the right, without further notice, to modify the specifications of its products at all times.

KUWAIT PETROLEUM INTERNATIONAL LUBRICANTS - NORTHWEST EUROPE

Technical Service
00800 786 45 787
www.Q8oils.com