

Q8 T 750

15W-40

Description

Super High Performance Diesel Engine Lubricant designed for lubrication of low emission Euro IV & Euro V engines.

Application

In all high performance four stroke diesel engines operating on low sulphur diesel fuel (<0.05 % mass) and under severe heavy duty conditions. Extended oil drain intervals as indicated by the OEM for high quality diesel engine oils can be applied.

The diesel engines may be normally aspirated, turbocharged or supercharged, with or without intercooling and fitted in commercial vehicles or off-highway equipment.

Suitable for application in passenger cars with gasoline or diesel engines.

#API CI-4/SL

#ACEA E7, E5, E3, B4, B3, A3

#Global DHD-1

#MAN M3275

#MB 228.3

#Volvo VDS-3

#MTU Type 2

#Renault VI RLD & RLD-2

#Deutz DQC III-10

#Cummins CES 20071, -72, -76, -77, -78

#Caterpillar ECF-1 & ECF-2

#Mack EO-M Plus

#ZF TE-ML 04C, 07C

#Exceeds requirements of DAF, IVECO and Scania

Benefits

- Excellent protection against bore polishing and cam wear
- Offers prolonged oil drain intervals and reduces maintenance costs
- Protects engine against corrosive wear in off-the-road applications
- Provides quick lubrication after cold starting thus limiting engine wear
- Prevents engine fouling due to combustion soot
- Performance quality allows wide application from cars to trucks
- Universal engine oil suitable for passenger cars, trucks and off-road applications

To be able to offer our clients products with constantly better characteristics, Kuwait Petroleum reserves the right, without further notice, to modify the specifications of its products at all times.

KUWAIT PETROLEUM INTERNATIONAL LUBRICANTS - NORTHWEST EUROPE

Technical Service
00800 786 45 787
www.Q8oils.com

Specifications

Specification	Method	Units	
Viscosity Grade			SAE 15W-40
Absolute Density, 15 °C	D 1298	kg/m ³	886
Kinematic Viscosity, 40 °C	D 445	mm ² /s	104.6
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.0
Viscosity Index	D 2270	-	135
Borderline Pumping Temperature	D 3829	°C	-25
Flash Point	D 93	°C	210
Pour Point	D 97	°C	-27
Total Base Number	D 2896	mg KOH/g	10.0
Sulphated Ash	D 874	% mass	1.4

To be able to offer our clients products with constantly better characteristics, Kuwait Petroleum reserves the right, without further notice, to modify the specifications of its products at all times.

KUWAIT PETROLEUM INTERNATIONAL LUBRICANTS - NORTHWEST EUROPE

Technical Service
00800 786 45 787
www.Q8oils.com