

Q8 T 905

10W-40

Description

High performance synthetic heavy duty engine oil with low sulphated ash, phosphorus and sulphur content (low SAPS) designed for lubrication of Euro 4, Euro 5 diesel engines.

Application

All Euro 4 & Euro 5 diesel engines equipped with a diesel particulate filter (DPF) or catalytic after treatment systems (such as SCR) operating on low sulphur diesel fuel (50 ppm or below) and under severe heavy duty conditions. Extended oil drain intervals as indicated by the OEM for high quality diesel engine oils can be applied.

For ACEA E6, ACEA E7 and ACEA E9 applications.

Also for all diesel engines requiring ACEA E4-99.

LowSAPS formulation suitable for certain gas engine applications

For mobile gas engines

Specifications

- ACEA E6 /E7 /E9
- API CI-4
- MAN M3477
- MB-Approval 228.51
- MTU type 3 & MTU type 3.1
- Renault VI RXD
- Volvo VDS-3
- Mack EO-M Plus
- Cummins CES 20076/20077
- DAF HP-2** ACEA E4 SAE 10W-40 products do not require DAF HP-2 testing for extended drain applications
- Volvo CNG
- Deutz DQC III-05
- Caterpillar ECF-1-a
- Renault VI RGD
- MAN 3271-1
- MB 226.9

Benefits

- Specially developed formulation for both ACEA E6, ACEA E7 and ACEA E9 applications
- Minimizes diesel particulate filter (DPF/CRT) plugging
- Protects catalytic after treatment systems (SCR)
- Excellent protection against bore polishing and cam wear
- Offers prolonged oil drain intervals and reduces maintenance costs
- Provides quick lubrication after cold starting thus limiting engine wear
- Prevents engine fouling due to combustion soot

To be able to offer our clients products with constantly better characteristics, Kuwait Petroleum reserves the right, without further notice, to modify the specifications of its products at all times.

KUWAIT PETROLEUM INTERNATIONAL LUBRICANTS - NORTHWEST EUROPE

Technical Service
00800 786 45 787
www.Q8oils.com

Specifications

Specification	Method	Units	
Viscosity Grade	-	-	SAE 10W-40
Absolute Density, 15 °C	D 1298	kg/m ³	860
Kinematic Viscosity, 40 °C	D 445	mm ² /s	95.7
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.0
Viscosity Index	-	-	149
Borderline Pumping Temperature	D 3829	°C	-24
Flash Point	D 93	°C	212
Pour Point	D 97	°C	-30
Total Base Number	D 2896	mg KOH/g	10
Sulphated Ash Content	D 874	% mass	1.0

To be able to offer our clients products with constantly better characteristics, Kuwait Petroleum reserves the right, without further notice, to modify the specifications of its products at all times.

KUWAIT PETROLEUM INTERNATIONAL LUBRICANTS - NORTHWEST EUROPE

Technical Service
00800 786 45 787
www.Q8oils.com